



386 Internationale Drive Suite H, Bolingbrook, Illinois 60440
 Tel: (708) 493-1191 Toll Free: (800) 379-1191 Fax: (630) 296-8100

Temperature Control SmartWire™

UL Listed and Rated Type CL3P or CMP
 Multi-Conductor Shielded Plenum Cable

P/N 004340 - 22 AWG 4 Conductor Shielded Plenum



Cable Specifications	
Description:	22 AWG 4 Conductor Bare Copper, Shielded Plenum, UL Subject 444, Type CL3P/CMP, C(UL)
Conductor Description:	22 (7/30 Bare Copper)
Insulation:	Low-Smoke PVC .007"
Color Code:	Black/White/Red/Green
Shield:	Overall Aluminum Mylar Foil - 100% Coverage
Drain Wire:	24 AWG 7 Strand Tinned Copper
Jacket:	Low-Smoke PVC .015"
Marking:	TEMPERATURE CONTROL SYSTEM AN BIN DIG IN / OUT A B C D E 0 1 2 3 4 5 6 7 8 9 22AWG 4C SHIELDED (UL) CL3P OR CMP C(UL)US 75°C FT-6 "ROHS"
Overall Diameter:	.159" Nom.
Conductor DCR:	N/A
Capacitance:	N/A
Impedance:	N/A
Temperature and Voltage Rating:	75 C / 300 Volt
Cable Weight:	19 Lbs/Mft.



Flame Rating:

Approved For Plenum Use Without Conduit Per NEC Article 800 by Passing UL-910 Steiner Tunnel Test

Agencies Approvals:

NEC Article 800, 725; UL CL3P/CMP, C(UL), RoHS Compliant

