



386 Internationale Drive Suite H, Bolingbrook, Illinois 60440  
 Tel: (708) 493-1191 Toll Free: (800) 379-1191 Fax: (630) 296-8100

**UL Listed and Rated Type CL3P or CMP  
 Single Pair Shielded Plenum Cable**

P/N **043006AL** - Automated Logic ARC156 Cable 22 AWG 1 Pair  
 Shielded Lo-Cap Plenum

Cable Specifications	
Description:	1 Pair, 22 AWG Tinned Copper Shielded RS-232, RS-422 Low-Capacitance Communication, Instrumentation and Special Application Plenum Cable
Conductor Description:	22 AWG (7/30) Tinned Copper
Insulation:	Foam FEP .0155"
Color Code:	Black/White
Shield:	Aluminum Mylar Foil
Drain Wire:	24 AWG Stranded Tinned Copper
Jacket:	.014" Plenum Rated PVC
Marking:	ARC156 A B C D E 0 1 2 3 4 5 6 7 8 9 LO-CAP 12.5 PF/FT CL3P OR CMP 22 AWG 75 C. (UL)
Overall Diameter:	.157" Nom.
Conductor DCR:	N/A
Capacitance:	12.5 pF/ft. Nom.
Impedance:	100 Ohms Nom.
Velocity of Propagation:	N/A
Temperature and Voltage Rating:	75 C / 300 Volt
Cable Weight:	18 Lbs/Mft.



**Flame Rating:**

Approved for Plenum use without conduit per NEC Article 725 by passing UL-910 Steiner Tunnel Test (USA)

**Agencies Approvals:**

UL Subject 13, 444, 910 and 1581, Type CL3P/CMP Communication Cable, (UL)

