



386 Internationale Drive Suite H, Bolingbrook, Illinois 60440  
 Tel: (708) 493-1191 Toll Free: (800) 379-1191 Fax: (630) 296-8100

**UL Listed and Rated Type CMP  
 Multi-Pair Non-Shielded Plenum Category 5e Cable**

P/N **555610** - 24 AWG 4 Pair Category 5e UTP Plenum Cable

Cable Specifications	
Description:	24 AWG Category 5e Unshielded Twisted Pair (UTP) Cable for Data Transmission up to 350 MHz. This cable is Plenum Rated and Verified to Category 5e Electricals
Conductor Description:	24 AWG Solid Bare Copper
Insulation:	3 Pairs = FEP, 1 Pair = Polyolefin
Color Code:	White-Blue/Blue, White-Orange/Orange, White-Green/Green, White-Brown/Brown
Jacket:	Low-Smoke PVC
Marking:	A B C D E 0 1 2 3 4 5 6 7 8 9 4pr24AWG Type CMP (UL) c(UL) ETL verified to TIA/EIA-568-B.2 UTP Cat.5e 350 MHz
Performance Data:	PD555610.htm
Max. Conductor DCR:	Ohms/100m (328 ft) @ 20°C 9.38 Max.
Max. Mutual Capacitance:	nF/100m (328 ft) @ 1kHz 5.60 Nom.
Characteristic Impedance:	1 - 100 MHz
Velocity of Propagation:	72% Nom.
Max. DCR:	Ohms/100m (328 ft) @ 20°C 9.38 Max.
Max. Propagation Delay:	45 ns/100m MAX.
Voltage:	300 Volts



**Flame Rating:**  
 Approved For Plenum Use Without Conduit Per NEC Article 800 by Passing UL-910 Steiner Tunnel Test (USA) and CSA CMP Test (Canada)

**Agencies Approvals:**  
 UL Listed Type CMP, ETL Verified to TIA 568-B.2 UTP Category 5e, C(UL)

